



Chafe-Pro®



APPLICATIONS

- Chafe abrasion protection for mooring, anchor, towing and ship assist lines
- Keep lines coiled
- Cover shroud/stay turnbuckles
- Keep sailed furled on booms
- Rock and mountain climbing
- High rise window washing

RANGE

- HB Eye Units available from 25mm - 127mm size
- Nylon Sleeves available from 17mm - 94mm
- Custom lengths
- Other specialist covers available on request

FEATURES

- Easy application and removal - Chafe Pro® is wrapped around the line to be protected and can be installed on lines already in position.
- Chafe Pro® can be installed or removed from the eye without having to undo the splice
- Chafe Pro® can be installed in an eye splice turned on a capstan or windlass, or heaved through a chock
- No lacing or lashing of lines is required due to a special locking feature
- High abrasion resistance
- High UV and mildew resistance
- Eye Units are coated to aid in holding the nylon weave together in areas where the chafing gear is stressed most by friction

FIBRE CHARACTERISTICS

Fibre Type	Description	Specific Gravity	Sensitive to	Resistant to	Heat Reaction	Strength & Elongation
Nylon (Polyamide)	Continuous Filament	1.14	Strong acids and oxidising agents, soluble in formic, sulphuric acids and phenolic compounds	Alkalis, alcohols, esters, hydrocarbons and most bleaches	Softens 229°C Melts 249°C - 260°C	Elongation Dry 40%. Wet 35%. 90-95% strength ratio wet/dry