



Compactor Paktwine



FEATURES

- Tough, strong synthetic lashing
- Abrasion resistant
- Soft feel with smooth handling
- UV stabilised for increased durability
- Low stretch with excellent knotting efficiency
- Safer and economical alternative to steel strapping

RANGE/TECHNICAL

- Red/Brown colour

APPLICATIONS

- Compacting
- Alternative to steel strapping

Product Code	Description	Tex	Pack Weight	Tensile Strength	Spools per Pack	Metres per spool
LAS0118M	Compactor Paktwine 1/165	6380	15.0 kg	230 kg	4	550
LAS0108M*	Contractor Paktwine 1/140	7300	19.0 kg	290 kg	2	1300

* Made to order. Minimum order quantity and lead time applies

FIBRE CHARACTERISTICS

Fibre Type	Description	Specific Gravity	Sensitive to	Resistant to	Heat Reaction	Strength & Elongation
PP (Polypropylene)	Continuous Filament	0.91	Sodium hypochlorite and some hot organic solvents. Very susceptible to sunlight but with suitable additives, loss of strength is retarded.	Hot and cold acids like alkalis	Shrinks rapidly from flame. Curls and melts at 165°C.	High tenacity. Good recovery from stretch and elongation at break for ropes is 25-30%