



Donaghys T12 Rigging Braid



FEATURES

- Excellent heat resistance
- High strength to weight ratio
- Great creep resistance
- Easy to splice
- Low Visibility
- Safer than wire (low recoil)

RANGE/TECHNICAL

- 12 strand Technora® braid
- Black colour - Abrasion resistant coating
- 3mm - 8mm

APPLICATIONS

- Theatrical
- Wire Replacement
- Guy and Stay line
- Tie off line
- Operating lines
- Standing rigging
- Camera ziplines
- Stunt rigging

Product Code	Description	Weight per 100m	Breakload (kg)
BRS030T12	T12 Rigging Braid 3mm	0.65	1000
BRS050T12	T12 Rigging Braid 5mm	1.8	2400
BRS060T12	T12 Rigging Braid 6mm	2.5	3400
BRS080T12	T12 Rigging Braid 8mm	4.2	5200

FIBRE CHARACTERISTICS

Fibre Type	Description	Specific Gravity	Sensitive to	Resistant to	Heat Reaction	Strength & Elongation
Technora	Spun Filament	1.39	Hydrochloric, hydrobromic and sulphuric acids, bleaching and sunlight.	Mineral and organic acids, alkalis, organic solvents, sea water and steam.	500°C+ decomposition	Equivalent wet/dry strength ratio. Elongation 4.5% at Break