



Paktwine Lashings



FEATURES

- A range of all purpose synthetic lashings
- Ease of handling
- Strong lightweight twines
- Chemically resistant
- Easily managed draw from centre

RANGE/TECHNICAL

- White colour

APPLICATIONS

- Suitable for a wide range of applications

Product Code	Description	Tex	Pack Weight	Tensile Strength	Spools per Pack	Metres per spool
LAS0112M	Paktwine Regular 1/700	1400	7.6 kg	60 kg	2	2600
LAS0110M	Paktwine Heavy 1/500	1970	8.0 kg	90 kg	2	1900
LAS0111M	Paktwine Premium 1/350	2830	7.4 kg	115 kg	2	1300
LAS0113M	Paktwine Super 1/200	4860	7.6 kg	170 kg	2	750
LAS0054	PP Lashing 1/200	5000	7.5 kg	170 kg	1	1500

FIBRE CHARACTERISTICS

Fibre:Type	Description	Specific Gravity	Sensitive to	Resistant to	Heat Reaction	Strength & Elongation
PP (Polypropylene)	Continuous Filament	0.91	Sodium hypochlorite and some hot organic solvents. Very susceptible to sunlight but with suitable additives, loss of strength is retarded.	Hot and cold acids like alkalis	Shrinks rapidly from flame. Curls and melts at 165°C.	High tenacity. Good recovery from stretch and elongation at break for ropes is 25-30%