



Silver Anchor Packs



FEATURES

- Soft but durable PE Silver Rope construction
- Easy on hands and deck coiling
- Pre spliced with minimum of 4 tucks to ensure reliability
- Stainless steel thimble for anchor attachment
- Floats in water
- Neat and uniform packaging for display in store
- Variety of sizes and lengths to suit all popular size vessels

RANGE/TECHNICAL

APPLICATIONS

- 6mm 12mm in 50m lengths
- 8mm 12mm in 110m lengths

	Anchoring
_	7 1110110111119

Code	Size (mm)	Length (m)	Colour	Unit	Coil Weight	App Break (kg)
PRP0645	6mm	50m	White	Coil	1.0 kg	375
PRP0846	8mm	50m	White	Coil	1.5 kg	620
PRP1041	10mm	50m	White	Coil	2.5 kg	945
PRP1218	12mm	50m	White	Coil	4.0 kg	1265
PRP0850	8mm	110m	White	Coil	3.3 kg	620
PRP1043	10mm	110m	White	Coil	4.9 kg	945
PRP1219	12mm	110m	White	Coil	8.0 kg	1265

^{*} Note: Splicing can reduce break by 10% as listed in AS4142:1 1993

FIBRE CHARACTERISTICS

Fibre:Type	Description	Specific Gravity	Sensitive to	Resistant to	Heat Reaction	Strength & Elongation
Polyethylene	Continuous Filament	0.95	Xyelene at 95°C, hot nitric or sulphuric acids, some hot organic solvents. Sensitive to prolonged sunlight exposure.	Most acids, alkalis, grease, oils and organic solvents	Softens 100°C Melts 110-120°C	High tenacity with good recovery after stretch and extension at break of 50%