



# Yachtmaster XS



## FEATURES / BENEFITS

- Double braid construction in 100% high-tenacity Polyester
- High jacket to core ratio assisting long life
- Excellent breakload, UV and abrasion resistance
- Resistant to kinking, hocking and twisting
- Highly resistant to most chemicals
- Easy to splice



## RANGE / TECHNICAL

- 4mm - 16mm
- 100m reels
- Bulk reels or cartons and larger diameters available on request
- Other colours available on request

## APPLICATIONS

- |                 |  |
|-----------------|--|
| ■ Sheets        | ■ Boom vang/kicker                                     |
| ■ Guys          | ■ Reefing and furling systems on cruiser/racing yachts |
| ■ Control lines | ■ General Industrial Applications                      |
| ■ Out/downhauls | ■ Cable Hauling  |
| ■ Runner tails  | ■ Lowering Lines                                       |
| ■ Traveller     |  |

## RANGE/TECHNICAL

Product Code	Description	Breaking Force (kg)	Weight kg/100m
RBRY0405	YACHTMASTER XS 4MMX100M WHITE	400	1.3
RBRY0515	YACHTMASTER XS 5MMX100M WHITE	660	2
RBRY0619	YACHTMASTER XS 6MMX100M BLUE FLK	900	3.5
RBRY0618	YACHTMASTER XS 6MMX100M GREEN FLK	900	3.5
RBRY0617	YACHTMASTER XS 6MMX100M RED FLK	900	3.5
RBRY0610	YACHTMASTER XS 6MMX100M WHITE	900	3.5
RBRY0812	YACHTMASTER XS 8MMX100M BLUE FLK	1700	5.3
RBRY08YA	YACHTMASTER XS 8MMX100M GOLD FLK	1700	5.3
RBRY0815	YACHTMASTER XS 8MMX100M GREEN FLK	1700	5.3
RBRY0813	YACHTMASTER XS 8MMX100M RED FLK	1700	5.3
RBRY0808	YACHTMASTER XS 8MMX100M WHITE	1700	5.3
RBRY0874	YACHTMASTER XS 8MMX200M WHITE	1700	10.6
RBRY1012	YACHTMASTER XS 10MMX100M BLUE FLK	2350	9
RBRY1013	YACHTMASTER XS 10MMX100M GREEN FLK	2350	9
RBRY1015	YACHTMASTER XS 10MMX100M RED FLK	2350	9
RBRY1008	YACHTMASTER XS 10MMX100M WHITE	2350	9
RBRY1039	YACHTMASTER XS 10MMX200M BLUE FLK	2350	18
RBRY10WB	YACHTMASTER XS 10MMX300M BLUE FLK	2350	27
RBRY1213	YACHTMASTER XS 12MMX100M BLUE FLK	3250	11.2
RBRY1210	YACHTMASTER XS 12MMX100M GREEN FLK	3250	11.2
RBRY1211	YACHTMASTER XS 12MMX100M RED FLK	3250	11.2
RBRY1205	YACHTMASTER XS 12MMX100M WHITE	3250	11.2
RBRY1407	YACHTMASTER XS 14MMX100M BLUE FLK	4200	16.2
RBRY1408	YACHTMASTER XS 14MMX100M RED FLK	4200	16.2
RBRY1606	YACHTMASTER XS 16MMX100M BLUE FLK	5600	17.6
RBRY1609	YACHTMASTER XS 16MMX100M RED FLK	5600	17.6

**Note: Manufactured & tested in accordance with ISO 10547:2009**

## FIBRE CHARACTERISTICS

Fibre type	Description	Specific gravity	Sensitive to	Resistant to	Heat reaction	Strength and elongation
<b>Polyester</b>	Continuous Filament	1.38	Alkalis, Phenolic Compounds, Sulfuric Acid.	Most Organic and Mineral Acids, Solvents, Bleaches and Oxidizing Agents.	Softens 228°C, Melts 255°C.	Equivalent wet/ dry strength ratio. Elongation 35% at Break.